

Sprinter Cargo Van

Room to work. Room to grow.





For those wanting more out of business, the Mercedes-Benz Sprinter Cargo Van delivers more. Its durable unibody construction offers Best-In-Class¹ payload capacity of up to 5,358 lbs., Best-In-Class¹ cargo capacity of up to 547 cu. ft., Best-In-Class¹ rear and side door openings and Best-In-Class¹ standing height² of 6'6". It not only allows you to carry and do more, it allows your business to become more.

Powered by a new 3.0 liter V6 turbo engine with BlueTEC SCR diesel technology, the Sprinter delivers incredible fuel economy and impressive power from one of the world's cleanest diesel engines.³ With more miles to the gallon and more miles between intervals of Sprinter Authorized Service, the cost of ownership is even more attractive.

Peace-of-mind comes standard with state-of-theart safety features like Adaptive ESP®4 with Load Adaptive Control & Roll Over Mitigation, ESP® Trailer Stability Assist and our unique Cargo Protection load-securing and lashing system. With available financing from Mercedes-Benz Financial, you've got a van designed to work smarter, courtesy of the world's leader in commercial vehicles.

To find a Sprinter dealer near you, go to MBSprinterUSA.com.




Sprinter Cargo Van

- ▶ 2 wheelbases, 3 body lengths, 2 cargo area heights, 3 Gross Vehicle Weight classes
- ▶ Class-leading cargo volume (318 to 547 cu. ft.) in the full-size van class
- ▶ Class-leading payload (2,855 to 5,358 lbs.) with available rear A/C
- ▶ Class-leading cargo area height (up to 78.2 inches)

2325

- ▶ Loading length up to 185 inches
- ▶ Towing capacity up to 7,500 lbs. and a tongue weight of up to 750 lbs.




Powertrain Specifications

BlueTEC SCR Diesel engine with AdBlue®3
EPA / CARB 2010 Compliant
6-cylinder, V 72°
4 valves per cylinder
Displacement 2,987 cc
188 hp at 3,800 rpm
Rated torque 325 lb-ft at 1,400-2,400 rpm
Rear-wheel drive
5-speed automatic transmission
Fuel type: Ultra low sulfur diesel
Tank capacity 26.4 gallons
Electronically controlled direct injection with common rail
Turbocharger and intercooler function



Battery 12 V/100 Ah, alternator 220 A



10 CARGO VAN MODELS	2500 STANDARD	2500 HIGH ROOF			3500 HIGH ROOF					
	144" WB	144" WB	170" WB	170 " WB Ext	144	·" WB	170	" WB	170"	WB Ext
Turning Diameter (ft) Wall To Wall	47.6	47.6	54.6	54.6	4	7.6	5	4.6	5	4.6
Ground To Sliding Door Step - Side	20.2	20.2	19.9	19.9		22	2	1.2	2	1.2
Load Height — Rear	27.6	27.6	27.4	27.2	3	1.1	3	0.9	3	0.9
Door Opening Height — Side	59.8	71.7	71.7	71.7	7	1.7	7	1.7	7	1.7
Door Opening Height — Rear	60.6	72.4	72.4	72.4	7	2.4	7	2.4	7	2.4
Door Opening Width - Side	51.2	51.2	51.2	51.2	5	1.2	5	1.2	5	51.2
Door Opening Width — Rear	61.6	61.6	61.6	61.6	6	1.6	6	1.6	6	1.6
Cargo Bed Length	128.5	128.5	169.3	185	12	28.5	16	59.3	1	85
Cargo Bed Width at Wheelhouse	53.1	53.1	53.1	53.1	3	8.5	3	8.5	3	8.5
Maximum Width at Floor	70.1	70.1	70.1	70.1	7	0.1	7	0.1	7	0.1
Interior Height	65	78.2 ²	78.2 ²	78.2 ²	78	8.2 ²	78	8.2 ²	7	8.22
Cargo Volume (cu ft)	318	371	494	547		371		94		547
Maximum Available GVWR (lb)	8,550	8,550	8,550	8,550	GVWR 9,990	GVWR 11,030 ⁵	GVWR 9,990	GVWR 11,030 ⁵	GVWR 9,990	GVWR 11,030 ⁵
Base Curb Weight (lb)	5,098	5,165	5,562	5,695	5,683	5,672	6,102	6,091	6,213	6,202
Maximum Payload (lb)	3,452	3,385	2,988	2,855	4,307	5,358	3,888	4,939	3,777	4,828
Maximum Available GCWR (lb)	13,550	13,550	13,550	13,550	14,990	15,250	14,990	15,250	14,990	15,250
Maximum Towing (lb)	5,000	5,000	5,000	5,000	7,	500	7,	500	5,	000
Fuel Tank Capacity (gal)	26.4	26.4	26.4	26.4	2	6.4	2	6.4	2	6.4

273.2

Inches Unless Otherwise Noted

Selected Optional Equipment Packages					
Accessory Package	High Idle Variable Package	Rear Air Conditioning Package			
Additional Battery Package	Interior Lighting Package	Rear Heating Packages I, II & III			
Cargo Package	Lighting Package	Security Package			
Cold Climate Package	Mobility Prep Package	Suspension Packages			
Contractor Package	Multi-function Wheel/Display Package	Suspension Seating Package			
Front Bench Seat Package	PARKTRONIC Package	Trailer Hitch Package			
Heavy Duty Front Axle Package	Partition with Sliding Door Package	Window Packages I, II, III & IV			
High Idle Fixed Package	Premium Package				

Some specifications and features shown or mentioned on this data sheet are optional and only available upon request at extra cost. Specifications are subject to change without notice.

Warning: the forces of a deploying air bag can cause serious or fatal injuries to a child under age 13. See Operator's Manual for additional warnings and information on air bags, seat belts and child seats.

¹ Based on a comparison of the Automotive News classification of full-size commercial vans.

² In base configuration.

³ Requires the use of ultra low sulfur diesel fuel. Mercedes-Benz Sprinters are approved to use B5 biodiesel (approved diesel fuel with a maximum 5% biodiesel content) in all BlueTEC engines. The only approved biodiesel content is one that meets ASTM D6751 specifications and has the oxidation stability necessary to prevent deposit-/corrosion-related damages to the system (min. 6h, proven by EN14112 method). Please see your service station for further information. If the B5 biodiesel blend does not clearly indicate that it meets the above standards, please do not use it. The Mercedes-Benz New Vehicle Limited Warranty does not cover damage caused by non-Mercedes-Benz

⁴ No system, regardless of how advanced, can overcome the laws of physics or correct careless driving. Please always wear your seat belt. Performance is limited by available traction, which snow, ice and other conditions can affect. Always drive carefully, consistent with conditions. Best performance in snow is obtained with winter tires. Read Operator's Manual before towing. In some states, aftermarket trailer brakes are required. See dealer for details.

⁵ Optional or part of an Option Package.